



# CONKLEEN 204

## Heavy Duty Concrete Cleaner

### DESCRIPTION

A unique water based concrete cleaner that removes rubber burn tire marks and heavy oils from concrete floors. This high active cleaner is fortified with alkaline builders, sequestrants, metal corrosion inhibitors, solubilizers and various detergents to insure rapid removal of grease and oil from the floors' surface.

### PRODUCT FEATURES / BENEFITS

- USDA authorized / May be used in federally inspected meat, dairy, egg and poultry processing plants
- Removes rubber burn marks / Replaces flammable solvent products for this application
- Contains water soluble solvents / Allows efficient removal of petroleum oils, grease and rubber tile burns
- Strong alkali buffered system / Added strength for removal of heavy food generated grease and oils but buffered for added safety and equipment compatibility
- Controlled foam / Excellent for use with automatic scrubbers and wet-vacuum systems

### DIRECTIONS FOR USE

The most effective aqueous cleaner for removing heavy oil and grease soils, and resistant rubber tire marks from concrete, terrazzo, stone, tile, brick, marble, magnesite, conductive cement, ceramic tile, steel, sealed wood, painted and similar hard surfaces. Also an outstanding general purpose cleaner, safe on all hard surfaces when diluted as per directions. Dilute concentrate with hot or cold water for use.

**General Cleaning:** Use 1 to 2 oz. per gallon of water.

**Heavy Duty Cleaning:** Use 1 pint per gallon of water.

**Rubber Tire Mark Removal:** use 1 quart per gallon of water.

Adjust the use level to provide the most effective cleaning of the soiling conditions found on each job.

Apply diluted cleaner with sponge, mop, brush, sprinkler, sprayer, foamer or automatic floor machine. For severe soiling, let soak as long as possible but do not allow floor to dry. Agitation helps to loosen severe soiling. Machines equipped with steel, fiber or nylon brushes, or abrasive pads are best for severely soiled areas. Where available a high pressure washer may suffice for agitation and assist in flushing away loosened soils. Rinse thoroughly two or more times if floor is being prepared for sealing, otherwise a single rinse is difficult.

### SPECIFICATIONS

Color.....	Green-Yellow
Odor.....	Pleasant
Active (%).....	21.0 ± 0.5
pH (Concentrate).....	12.7 ± 0.5
pH (Use Dilution).....	10.7 ± 0.5
Solubility.....	Complete in Water
Specific Gravity (gr/cc).....	1.045
Density (lbs/gal).....	8.71
High Temp. Cloud.....	> 125°F
Low Temp. Cloud.....	< 32°F

Freeze-Thaw Stable.....	Yes
Flash Point.....	None
Toxic Solvent Fumes.....	None
Free Rinsing.....	Yes
Biodegradable.....	Yes
Phenols or Cresols.....	None
Corrosive.....	No (Slight on Aluminum)
Detergency.....	Unique Deep Cleaning
Oil Emulsification.....	Excellent
Shelf Life.....	1 year minimum in original unopened container

### SAFETY INFORMATION

**WARNING:** IRRITANT; HARMFUL IF SWALLOWED. CAUSES SKIN AND EYE IRRITATION. Avoid contact with skin, eyes and clothing. Do not ingest. May cause severe mucosal damage and gastric distress. May cause systemic intoxication.

**FIRST AID: For Eyes:** Flush eyes with water for at least fifteen minutes. Seek medical attention. **For Skin:** Wash thoroughly with water and apply emollient creme. If irritation persists seek

medical attention. Wash all contaminated clothing prior to reuse. **If ingested:** Do not induce vomiting. Give milk, egg white, gelatin, or large quantities of water. Seek immediate medical attention.

Authorized by USDA for use in federally inspected meat and poultry plants.

FOR PROFESSIONAL USE ONLY



HMIS HAZARD CODE	
2	HEALTH
0	FLAMMABILITY
0	REACTIVITY
0	PERSONAL PROTECTION



401 N. 10th Street · Philadelphia, PA 19123  
1-800-NAT-CHEM · 215-922-1200 · FAX: 215-922-5517  
www.nclonline.com · e-mail:info@nclonline.com