# SAFETY DATA SHEET.

Issuing date 27-May-2015 Revision Date 16-Nov-2018 Version 3.01

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

**Product name** 6749-0 GARAGE DOOR LUBE 12 PK

Recommended use of the chemical

and restrictions on use

Product code F03256

Product Type Extremely Flammable Aerosol

Synonyms None

Supplier's details

Recommended Use

Uses advised against No information available

Manufactured For: Manufacturer

Imperial Supplies LLC American Jetway Corporation

789 Armed Forces Drive 34136 Myrtle Street
P.O. Box 11008 Wayne, MI 48184-0126
Green Bay, WI 53407-1008 Phone: (734) 721-5930

1-800-558-2808

Emergency telephone number

Chemical Emergency Phone CHEMTREC: 1-800-262-8200 ID 1195 (UNITED STATES)

Number CHEMTREC: +1-703-527-3887 (INTERNATIONAL)

## 2. HAZARDS IDENTIFICATION

#### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2B
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable Aerosols	Category 1
Gases under pressure	Compressed Gas

# GHS Label elements, including precautionary statements

#### **Emergency Overview**

#### DANGER

#### Hazard Statements

Causes skin irritation.

Causes eye irritation.

May cause respiratory irritation. May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Extremely Flammable Aerosol

Contains gas under pressure; may explode if heated



Appearance Opaque

Physical state Aerosol

Odor Solvent

#### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling.

Wear eye protection / face protection / protective gloves

Avoid breathing fumes, gas, mist, vapors, spray.

Use only outdoors or in a well-ventilated area.

Keep away from heat, sparks, open flames, hot surfaces - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

#### **Precautionary Statements - Response**

Specific treatment (see first aid on this label).

IF IN EYES:Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice, attention

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice, attention.

Take off contaminated clothing and wash it before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor, physician if you feel unwell.

IF SWALLOWED: Immediately call a POISON CENTER, doctor, physician.

Do NOT induce vomiting.

## **Precautionary Statements - Storage**

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

#### **Precautionary Statements - Disposal**

Dispose of contents, container to an approved waste disposal plant.

## Hazards not otherwise classified (HNOC)

None

#### Other information

0.000019% of the mixture consists of ingredient(s) of unknown toxicity.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
HYDROTREATED LIGHT DISTILLATES	64742-47-8	20-30
NAPHTHENIC OIL, SEVERLY HYDROT	64742-52-5	20-30
KEROSENE	8008-20-6	10-20
PETROLEUM DISTILLATES	64742-47-8	10-20
POLYMERIC VISCOSITY MODIFIER	MIXTURE	1-10
2-BUTOXYETHANOL	111-76-2	1-10
CARBON DIOXIDE	124-38-9	1-10
ETHYLENE GLYCOL	107-21-1	<0.1
NAPHTHALENE	91-20-3	<0.1

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

#### First aid measures for different exposure routes

General advice Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.

Eye contact Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove

any contact lenses and continue flushing. If eye irritation persists, consult a doctor.

**Skin contact** Wash off with soap and plenty of water. If skin irritation persists, call a physician. Remove

and wash contaminated clothing before re-use.

**Inhalation** Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped,

contact emergency medical services immediately.

Ingestion Call a physician or Poison Control Center immediately. Do NOT induce vomiting. Never

give anything by mouth to an unconscious person. Risk of product entering the lungs on

vomiting after ingestion.

#### Most important symptoms/effects, acute and delayed

Main Symptoms Causes skin irritation. Causes eye irritation. May cause respiratory irritation. May cause

drowsiness or dizziness. May be fatal if swallowed and enters airways.

## Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

Revision Date 16-Nov-2018

**Suitable Extinguishing Media** 

Water fog.Dry chemical. Foam.Carbon dioxide (CO2). Cool containers/tanks with water spray.

**Unsuitable Extinguishing Media** Do not use a solid water stream as it may scatter and spread fire. Keep away from sources of ignition - No smoking.

## Specific hazards arising from the chemical

Extremely Flammable / Flammable. Keep product and empty container away from heat and sources of ignition. In the event of fire and/or explosion do not breathe fumes. Keep containers and surrounding areas cool with water spray. In the event of fire, cool tanks with water spray.

**Explosion Data** 

Sensitivity to Mechanical Impact none.
Sensitivity to Static Discharge Yes.

**Protective Equipment and Precautions for Firefighters** 

In the event of fire and/or explosion do not breathe fumes. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Use with adequate ventiliation to keep the exposure levels below the OELS. Follow safe

handling advice and personal protective equipment recommendations.

Environmental precautions

Environmental precautions Vapors can accumulate in low areas. Report spills as required by local and federal

regulations. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system. Should not be released into the environment.

Methods and materials for containment and cleaning up

**Methods for Containment** Absorb with earth, sand or other non-combustible material and transfer to containers for

later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to

contaminate ground water system. Prevent product from entering drains.

Methods for cleaning up Soak up with inert absorbent material. Contain liquid and collect with an inter,

non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

## 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away

from open flames, hot surfaces and sources of ignition. Contents under pressure. Do not puncture or incinerate cans. Handle in accordance with good industrial hygiene and safety

practice. Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out

of the reach of children. Store locked up.

**Incompatible products**Strong acids, alkalis, oxidizing agents.

3

Aerosol Level

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Exposure Guidelines** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
HYDROTREATED LIGHT DISTILLATES 64742-47-8	TWA: 200 PPM 8 hours	-	-
KEROSENE 8008-20-6	TWA: 200 mg/m³ total hydrocarbon vapor application restricted to conditions in which there are negligible aerosol exposures  Skin - potential significant contribution to overall exposure by the cutaneous route	-	TWA: 100 mg/m³
2-BUTOXYETHANOL 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m³
CARBON DIOXIDE 124-38-9	STEL: 30000 ppm TWA: 5000 ppm	TWA: 5000 ppm TWA: 9000 mg/m³ (vacated) TWA: 10000 ppm (vacated) TWA: 18000 mg/m³ (vacated) STEL: 30000 ppm (vacated) STEL: 54000 mg/m³	IDLH: 40000 ppm TWA: 5000 ppm TWA: 9000 mg/m³ STEL: 30000 ppm STEL: 54000 mg/m³
ETHYLENE GLYCOL 107-21-1	STEL: 50 ppm vapor fraction STEL: 10 mg/m³ inhalable particulate matter, aerosol only TWA: 25 ppm vapor fraction	(vacated) Ceiling: 50 ppm (vacated) Ceiling: 125 mg/m³	-
NAPHTHALENE 91-20-3	TWA: 10 ppm Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 10 ppm TWA: 50 mg/m³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m³ STEL: 15 ppm STEL: 75 mg/m³

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Exposure controls** 

Engineering Measures Ventilation systems. Use adequate ventilation to keep the exposure levels below the

occupational exposure limits. Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Tightly fitting safety goggles.

**Skin and body protection** Chemical resistant apron. Protective gloves.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

## **Physical and chemical properties**

Physical state Aerosol

**Appearance** Opaque Odor Solvent

**Odor Threshold** Color hazy

Remarks • Methods **Property** Values No information available

Hq Melting/freezing point

No information available

Boiling point/boiling range

49 °C / 120 °F Flash Point (based on components)

**Evaporation rate** No information available Flammability (solid, gas) No information available

Flammability Limits in Air upper flammability limit lower flammability limit

Vapor pressure Vapor density

**Specific Gravity** 0.852

Water solubility No information available

Partition coefficient: n-octanol/water

**Autoignition temperature Decomposition temperature**  No information available

No information available

**Viscosity Explosive properties** 

Other information

VOC Content(%) 35.38

# 10. STABILITY AND REACTIVITY

Not applicable

## Reactivity

Stable under recommended storage conditions

## **Chemical stability**

Stable under recommended storage conditions.

## Possibility of hazardous reactions

None under normal processing.

#### **Conditions to Avoid**

Heat, flames and sparks. Exposure to air or moisture over prolonged periods.

# **Incompatible Materials**

Strong acids, alkalis, oxidizing agents.

#### **Hazardous Decomposition Products**

Carbon oxides, Hydrocarbons, Fumes.

## 11. TOXICOLOGICAL INFORMATION

# Information on likely routes of exposure

## **Product Information**

Inhalation May cause respiratory irritation, May cause drowsiness or dizziness.

\_\_\_\_\_

**Eye contact** Causes eye irritation.

**Skin contact** Causes skin irritation.

**Ingestion** May be fatal if swallowed and enters airways.

**Component Information** 

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
HYDROTREATED LIGHT DISTILLATES 64742-47-8	> 5000 mg/kg(Rat)	> 2000 mg/kg(Rabbit)	> 5.2 mg/L (Rat)4 h
NAPHTHENIC OIL, SEVERLY HYDROT 64742-52-5	> 5000 mg/kg(Rat)	> 2000 mg/kg(Rabbit)	-
KEROSENE 8008-20-6	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
PETROLEUM DISTILLATES 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
2-BUTOXYETHANOL 111-76-2	= 470 mg/kg ( Rat )	= 99 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h = 486 ppm ( Rat) 4 h
ETHYLENE GLYCOL 107-21-1	= 4700 mg/kg (Rat)	= 10600 mg/kg (Rat)	-
NAPHTHALENE 91-20-3	= 1110 mg/kg (Rat)	= 1120 mg/kg ( Rabbit )	> 340 mg/m³ (Rat) 1 h

## Information on toxicological effects

Symptoms Causes skin and eye irritation. May cause respiratory irritation. May cause drowsiness and

dizziness. May be fatal if ingested and enters airways.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationIrritating to skin.Eye damage/irritationIrritating to eyes.SensitizationNot a known sensitizer.Germ cell mutagenicityNot a germ cell mutagen.

Carcinogenicity The table below indicates whether each agency has evaluated a listed ingredient as a

carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
KEROSENE	A3	Group 3	-	-
8008-20-6		•		
2-BUTOXYETHANOL	A3	Group 3	-	-
111-76-2		•		
NAPHTHALENE	A3	Group 2B	Reasonably Anticipated	X
91-20-3		*		

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer) Group 3 - Not Classifiable as to Carcinogenicity in Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity

This product does not contain any known or suspected reproductive hazards.

Specific target organ systemic May cause respiratory irritation. May cause drowsiness and dizziness. toxicity (single exposure)

Specific target organ systemic toxicity (repeated exposure)

No known effect based on information supplied.

**Chronic toxicity**Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and

potential cardiac arrest.

Target Organ Effects Skin, Eyes, Respiratory System, and Central Nervous System.

Neurological effects Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal.

**Aspiration hazard** May be fatal if swallowed and enters airways.

# Numerical measures of toxicity - Product Information

## F03256 - 6749-0 GARAGE DOOR LUBE 12 PK

**Unknown Acute Toxicity** 0.000019% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)
ATEmix (dermal)
ATEmix (inhalation-dust/mist) 3381 mg/kg 11563 mg/kg 31.7 mg/l ATEmix (inhalation-vapor) 10.1 mg/l

# 12. ECOLOGICAL INFORMATION

## **Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to	Toxicity to daphnia and
			microorganisms	other aquatic invertebrates
HYDROTREATED LIGHT	-	45 mg/L LC50 Pimephales	-	-
DISTILLATES		promelas 96h flow-through		
64742-47-8		2.2 mg/L LC50 Lepomis		
		macrochirus 96h static 2.4		
		mg/L LC50 Oncorhynchus		
		mykiss 96h static		
NAPHTHENIC OIL,	-	5000 mg/L LC50	-	1000 mg/L EC50 Daphnia
SEVERLY HYDROT		Oncorhynchus mykiss 96h		magna 48h
64742-52-5				
PETROLEUM DISTILLATES	-	45 mg/L LC50 Pimephales	-	-
64742-47-8		promelas 96h flow-through		
		2.2 mg/L LC50 Lepomis		
		macrochirus 96h static 2.4		
		mg/L LC50 Oncorhynchus		
		mykiss 96h static		
2-BUTOXYETHANOL	_	1490 mg/L LC50 Lepomis	_	1000 mg/L EC50 Daphnia
111-76-2		macrochirus 96h static 2950		magna 48h
111702		mg/L LC50 Lepomis		magna 40m
		macrochirus 96h		
CARBON DIOXIDE		0.46 mg/L LC50		
124-38-9	-	Oncorhynchus mykiss	-	-
ETHYLENE GLYCOL	6500 - 13000 mg/L EC50	41000 mg/L LC50		46300 mg/L EC50 Daphnia
1	Pseudokirchneriella		<del>-</del>	
107-21-1		Oncorhynchus mykiss 96h		magna 48h
	subcapitata 96h	14 - 18 mL/L LC50		
		Oncorhynchus mykiss 96h		
		static 27540 mg/L LC50		
		Lepomis macrochirus 96h		
		static 40761 mg/L LC50		
		Oncorhynchus mykiss 96h		
		static 40000 - 60000 mg/L		
		LC50 Pimephales promelas		
		96h static 16000 mg/L LC50		
		Poecilia reticulata 96h static		
NAPHTHALENE	-	5.74 - 6.44 mg/L LC50	-	2.16 mg/L LC50 Daphnia
91-20-3		Pimephales promelas 96h		magna 48h 1.96 mg/L EC50
		flow-through 1.6 mg/L LC50		Daphnia magna 48h Flow
		Oncorhynchus mykiss 96h		through 1.09 - 3.4 mg/L
		flow-through 0.91 - 2.82		EC50 Daphnia magna 48h
		mg/L LC50 Oncorhynchus		Static
		mykiss 96h static 1.99 mg/L		
		LC50 Pimephales promelas		
		96h static 31.0265 mg/L		
		LC50 Lepomis macrochirus		
		96h static		

# Persistence and degradability

## **Bioaccumulation**

Chemical Name	log Pow
2-BUTOXYETHANOL	0.81

#### F03256 - 6749-0 GARAGE DOOR LUBE 12 PK

Revision Date 16-Nov-2018

111-76-2	
ETHYLENE GLYCOL 107-21-1	-1.93
NAPHTHALENE 91-20-3	3.6

Other adverse effects

No information available

## 13. DISPOSAL CONSIDERATIONS

## Waste treatment

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261). Dispose of in accordance with federal, state, and local regulations. Dispose of in accordance with federal, state, and local regulations. This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261.) Dispose of in accordance

with federal, state, and local regulations.

**Contaminated packaging** Do not re-use empty containers.

## 14. TRANSPORT INFORMATION

**DOT Ground** CONSUMER COMMODITY ORM-D

or

LIMITED QUANTITY

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD.QTY.

IMDG UN1950, AEROSOLS, 2.1, LTD.QTY

# 15. REGULATORY INFORMATION

## **International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
HYDROTREATED LIGHT DISTILLATES	Х	Х	X	Not listed	Х	Х	Х	Х
NAPHTHENIC OIL, SEVERLY HYDROT	Х	Х	Х	Not listed	Х	Х	Х	Х
KEROSENE	Х	X	Х	Х	X	X	X	Х
PETROLEUM DISTILLATES	Х	Х	Х	Х	Х	Х	Х	Х
2-BUTOXYETHANOL	Х	Х	Х	Х	Х	Х	Х	Х
CARBON DIOXIDE	Х	Х	Х	Х	Х	Х	Х	Х
ETHYLENE GLYCOL	Х	Х	Х	Х	Х	X	Х	Х
NAPHTHALENE	Х	Х	Х	Х	Х	Х	Х	Х

Leaend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

# U.S. Federal Regulations

## **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
2-BUTOXYETHANOL - 111-76-2	111-76-2	1-10	1.0
ETHYLENE GLYCOL - 107-21-1	107-21-1	<0.1	1.0
NAPHTHALENE - 91-20-3	91-20-3	<0.1	0.1

## SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

#### **Clean Water Act**

This product does contain the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
NAPHTHALENE 91-20-3	100 lb	X	Х	Х

# **CERCLA**

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
ETHYLENE GLYCOL 107-21-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
NAPHTHALENE 91-20-3	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

## **U.S. State Regulations**

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals:

Ethylene Glycol CAS # 107-21-1) is considered a Proposition 65 chemical for developmental only when ingested. The purpose of this product is not for ingestion.



This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Chemical Name		California Prop. 65	
	ETHYLENE GLYCOL - 107-21-1	Developmental (ingested) <0.1%	

NAPHTHALENE - 91-20-3	Cancer/<0.1%	

## **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
KEROSENE	X	X	X
8008-20-6			
2-BUTOXYETHANOL	X	X	X
111-76-2			
CARBON DIOXIDE	X	X	X
124-38-9			
ETHYLENE GLYCOL	X	X	X
107-21-1			
NAPHTHALENE	X	X	X
91-20-3			

**EPA Pesticide Registration Number** Not applicable

## Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

# **16. OTHER INFORMATION**

Instability 0 NFPA Health Hazard 2 Flammability 4 Physical and chemical

hazards -

Personal protection B **Health Hazard** 2\* Flammability 4 **Physical Hazard** 1 Chronic Health Star Hazard Repeated or prolonged exposure may cause central nervous system Chronic Hazard Star Legend

American Jetway Corporation **Prepared By** 

34136 Myrtle Street

Wayne, MI 48184-0126

27-May-2015 Issuing date **Revision Date** 16-Nov-2018

**Revision Note** 

## **Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a quide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**