Revision Date:

1.0051 04/11/2018

Fastball Page 1 of 7

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: **Fastball**

PRODUCT USE: All purpose cleaner

MANUFACTURED FOR: Warsaw Chemical Holdings LLC.

> P.O. Box 858 Warsaw, IN 46581

INFORMATION PHONE: Tel: 1-800-548-3396

P.O. BOX 858 • Warsaw, Indiana 46581 ® 800-548-3396 • www.warsaw-chem.com

Fax: 1-574-267-3884

INFOTRAC EMERGENCY PHONE:

> 1-800-535-5053 USA & Canada 352-323-3500 International

SECTION 2 - HAZARD(S) IDENTIFICATION

CLASSIFICATION: Skin Corrosion: Category 2

Eye Damage: Category 2B

PICTOGRAMS:

GHS ELELMENTS:

SIGNAL WORD: Warning

HAZARD STATEMENT(S): H315 | Causes skin irritation.

H320 | Causes eye irritation.

PRECAUTIONARY STATEMENT(S): P264 | Wash any exposed body parts thoroughly after handling.

P280 | Wear protective gloves/protective clothing/eye protection/face

P302 + P352 | IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P321 | Specific treatment (see supplemental first aid instruction on this label)

if immediate administration of antidote/specific measures/cleansing

agent/immediate measures is/are appropriate/required).

P333 + P313 | If skin irritation or rash occurs: Get medical advice/attention.

P337 + P313 | If eye irritation persists: Get medical advice/attention.

P362 | Take off contaminated clothing and wash before reuse.

None Known ADDITIONAL PRECAUTIONS:

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS



Fastball
Page 2 of 7

 Version:
 1.0051

 Revision Date:
 04/11/2018

 Print Date:
 03/02/2023

2-Butoxyethanol 111-76-2 Solvent 10 - 20% Surfactant 68130-47-2 Surfactant 1 - 5% 1310-73-2 < 1.0% Sodium Hydroxide 50% pH Adjustment Tetrasodium FDTA 64-02-8 Water Softener < 1.0% Pine Oil 8002-09-3 Fragrance < 1.0% Lemon Yellow 316 not available Colorant < 1.0% Acid Blue 145 Not Available Colorant < 1.0%

The chemical identity of some or all components is confidential business information (trade secret) and is being withheld as permitted by 29CFR19191200 (i). No other ingredients known to be hazardous.

SECTION 4 - FIRST AID MEASURES

EYES: Check for and remove contact lenses. Immediately flush eyes with plenty of

water for at least 15 minutes, occasionally lifting the upper and lower eyelids.

Get medical attention immediately.

SKIN: Wash skin surfaces thoroughly after contact. Wash clothing and clean shoes

thoroughly before reuse. Get medical attention if irritation develops.

INHALATION: Move exposed person to fresh air. If breathing is irregular or if respiratory

arrest occurs, provide artificial respiration or oxygen by trained personnel.

Loosen clothing. Get medical attention immediately.

INGESTION: Wash out mouth with water. Do not induce vomiting unless directed to do so

by medical personnel. Never give anything by mouth to an unconscious

person. Get medical attention immediately.

GENERAL: Physicians: No specific treatment. Treat symptomatically. Contact poison

treatment specialist if large quantities have been inhaled or ingested.

See Section 11 for exposure symptoms.

SECTION 5 - FIRE FIGHTING MEASURES

FLAMMABILITY: In a fire or if heated, a pressure increase will occur and the container may

burst.

EXTINGUISHING MEDIA: Use an extinguishing agent suitable for the surrounding fire.

PROTECTIVE EQUIPMENT: Fire-fighters should wear appropriate protective equipment and self-contained

breathing apparatus (SCBA) with full face-piece operated in positive pressure

mode.

ADDITIONAL INFORMATION: Thermal decomposition products-carbon monoxide, sulfur oxides, metal

oxide/oxides, halogenated compounds.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: No action should be taken involving individual risk or without suitable training.

Isolate area. Avoid contact with material. Do not breathe vapors. Provide

adequate ventilation. Wear proper personal protective equipment.

ENVIRONMENTAL: Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform relevant authorities if the product

Warsaw Chemical HOLDINGS LLC
P.O. BOX 858 · Warsaw, Indiana 46581
800-548-3396 · www.warsaw-chem.com

Version: Revision Date: Print Date: Page 3 of 7 1.0051 04/11/2018

Fastball

reaches sewers, waterways or soil.

CONTAINMENT/CLEANUP:

Stop leak if without risk. Move containers from spill area. Contain or absorb with inert dry material. Dispose of according to local regulations. See Section 1 for emergency contact information and 13 for waste disposal.

SECTION 7 - HANDLING AND STORAGE

SAFE HANDLING: Wear appropriate personal protective equipment (see Section 8). Eating

drinking and smoking should be prohibited. Do not get into eyes or on skin. Do not ingest. Keep containers tightly closed. Do not reuse container.

SAFE STORAGE: Store in accordance with local regulations. Store in original container away

from foods, drink and incompatible materials. Keep container tightly closed.

Do not store unlabeled. Use appropriate containment.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Apply technical measures to comply with occupational exposure limits.

Mechanical ventilation, eyewash stations, showers where necessary.

EYE PROTECTION: Safety eye-wear/face shield complying with an approved standard should be

used when a risk assessment indicates this is necessary to avoid exposure to

liquid splashes, mists or dusts.

RESPIRATORY PROTECTION: Use a properly fitted air-purifying or air-fed respirator complying with an

approved standard if a risk assessment indicates necessity. Respirator selection must be based on known or anticipated exposure levels, the hazards

of the product & the safe working limits of the chosen respirator.

HAND PROTECTION: Chemical resistant, impervious gloves complying with an approved standard

should be worn at all times when handling chemical products if a risk

assessment indicates this is necessary.

SKIN PROTECTION: Personal protective equipment for the body should be selected based on the

task being performed and the risks involved and should be approved by a

specialist before handling this product.

OSHA/ACGIH STEL COMPONENT: ACGIH TWA ppm OSHA/NIOSH STEL ppm mg/m3 2-Butoxyethanol 20.00 None None Surfactant None None 1.00 Sodium Hydroxide 50% 2.00 None None Tetrasodiúm EDTA None None 15.00 Pine Oil None None None Lemon Yellow 316 None None None Acid Blue 145 None None None

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid UPPER EXPLOSIVE LIMITS: NA

Fastball Page 4 of 7 1.0051

Revision Date:

04/11/2018

P.O. BOX 858 • Warsaw, Indiana 46581 ® 800-548-3396 • www.warsaw-chem.com Print Date: Clear yellow-green LOWER EXPLOSIVE LIMITS: NA

ODOR: Pine **VAPOR PRESSURE:** NA

ODOR THRESHOLD: NA VAPOR DENSITY: NA

PH: 11.5 - 14.0 RELATIVE DENSITY: NA

MELTING POINT: NA SOLUBILITY: Completely Water

Soluble

FREEZING POINT: NA

COLOR:

PARTITION COEFFICIENT: NA **BOILING POINT:** NA

AUTO-IGNITION TEMPERATURE: NA FLASH PT METHOD: NA

DECOMPOSITION TEMPERATURE: NA FLASH POINT: NA

SPECIFIC GRAVITY: 0.95000

EVAPORATION RATE: NA % VOLATILE: 10.20000

FLAMMABILITY: Nonflammable VISCOSITY (cst): NA

SECTION 10 - STABILITY AND REACTIVITY

REACTIVITY: HAZARDOUS DECOMPOSITION PRODUCTS

CHEMICAL STABILITY: Stable under normal conditions.

POSSIBILITY OF HAZARDOUS

REACTIONS:

Non-reactive.

CONDITIONS TO AVOID: Excessive heat or open flame.

INCOMPATIBLE MATERIALS: Avoid contact with acidic materials and strong oxidizers.

HAZARDOUS DECOMPOSITION

PRODUCTS:

Under normal conditions, none are known.

SECTION 11 - TOXICOLOGICAL INFORMATION

ROUTES OF ENTRY: Inhalation Absorption Ingestion

ACUTE EXPOSURE HAZARDS:

EYE CONTACT: Irritation, stinging, redness, burns.

DERMAL: Irritation, burns upon prolonged exposure.

ORAL: Nausea, vomiting.

INHALATION: No expected route of entry. Irritation.

2-Butoxyethanol (CAS No. 111-76-2)

Oral LD50: Rat 470 mg/kg



Page 5 of 7

1.0051 Revision Date: 04/11/2018 Print Date:



Surfactant (CAS No. 68130-47-2) Oral LD50: Rat 3.95 mg/kg

Tetrasodium EDTA (CAS No. 64-02-8) Oral LD50: 630-1,260mg/kg, rat

SECTION 12 - ECOLOGICAL INFORMATION

ECOTOXICITY: No data available.

PERSISTENCE & DEGRADABILITY: No data available.

BIOACCUMULATIVE POTENTIAL: No data available.

MOBILITY IN SOIL: No data available.

OTHER ADVERSE EFFECTS: No data available.

2-Butoxyethanol (CAS No. 111-76-2)

Fish LC50: 1250mg/L, 96h, Inland Sólverside Crustacean LC50: Daphnia 1818 mg/L 24h

Surfactant (CAS No. 68130-47-2) Fish LC50: Rainbow trout 5.5 mg/kg 96h

Sodium Hydroxide 50% (CAS No. 1310-73-2)

Fish LC50: 144mg/L, 96H guppy Tetrasodium EDTA (CAS No. 64-02-8) Fish LC50: 410mg/kg, 96h, bluegill

Pine Oil (CAS No. 8002-09-3)

Crustacean LC50: 17-28 mg/L 48h Daphnia

SECTION 13 - DISPOSAL CONSIDERATION

Material that cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Processing, use or contamination of the product may change the waste management options. Waste generators must decide if discarded material is a hazardous waste. State and local disposal regulations may differ from federal disposal definitions. Dispose of container and unused contents in accordance with federal, state and local requirements.

SECTION 14 - TRANSPORT INFORMATION

DOT (US)

UN NUMBER: NA

SHIPPING NAME: NA

TECHNICAL NAME: NA

HAZARD CLASS: NA

PACKAGING GROUP: NA

Fastball Page 6 of 7

> 1.0051 04/11/2018

Revision Date: Print Date:

P.O. BOX 858 • Warsaw, Indiana 46581 ® 800-548-3396 • www.warsaw-chem.com

SECTION 15 - REGULATORY INFORMATION

SARA 313 COMPONENTS CAS NO. % LESS THAN

2-Butoxyethanol 111-76-2 10 - 20%

CALIFORNIA PROP. 65 COMPONENTS CAS NO. % LESS THAN

10 - 20% 2-Butoxyethanol 111-76-2 Tetrasodium EDTA < 1.0% 64-02-8 Nonylphenol ethoxylate 127087-87-0 < 1.0%

This product can expose you to Ethylene Glycol, which is known to the State of California to cause birth defects or other reproductive harm...

RQ 1,000#

contains Nitrilo Acetic Acid <0.3% max and arsenic (max 1ppm) as contaminants or bi-products which are known to the State of

California to cause cancer or reproductive toxicity as listed under Prop. 65 State Drinking Water and

Toxic Enforcement Act.

127087-87-0 Nonylphenol polyethylene glycol ether 90 - 100 %

25322-68-3 Polyethylene glycol 1 - 5 %

123-91-1 1.4-Dioxane 0 - 0.1 %

64-19-7 Acetic acid 0 - 0.1 %

75-21-8 Ethylene oxide 0 - 0.1 %

RTK: MA, PĂ, NJ,

WARNING! This product contains a chemical known to the

State of California to cause cancer birth defects or other reproductive

123-91-1 1,4-Dioxane 0 - 0.1 %

64-19-7 Acetic acid 0 - 0.1 %

75-21-8 Ethylene oxide 0 - 0.1 %

SECTION 16 - OTHER INFORMATION

HAZARDOUS MATERIAL INFORMATION SYSTEM (U.S.A.)

Health Hazard	2
Fire Hazard	0
Reactivity	0
Personal Protection	В

Caution: HMIS ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks and 4 representing significant hazards or risks.

- A Safety Glasses
 B Safety Glasses, Gloves
 C Safety Glasses, Gloves, Apron
 D Face Shield, Gloves, Apron

- Safety Glasses, Gloves, Dust Respirator Safety Glasses, Gloves, Apron, Dust Respirator Safety Glasses, Gloves, Vapor Respirator
- Splash Goggles, Gloves, Apron, Dust & Vapor Respirator
- Safety Glasses, Gloves, Dust & Vapor Respirator Splash Goggles, Gloves, Apron, Dust & Vapor Respirator Airline Hood or Mask, Gloves, Full Suit, Boots
- Consult your supervisor for special handling directions

Flammability




Fastball
Page 7 of 7

 Version:
 1.0051

 Revision Date:
 04/11/2018

 Print Date:
 03/02/2023

NATIONAL FIRE PROTECTION ASSOCIATION (U.S.A.)



NFPA warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health, and reactivity hazards of chemicals.

Information on this form is furnished soley for the purpose of compliance with the Occupational Safety and Health Act of 1970 and shall not be used for any other purpose. Use or dissemination of all or any part of this information can be grounds for legal action.

To the best of our knowledge, the information provided in this Safety Data Sheet is accurate as of the date of its issue. However, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE. The information this Safety Data Sheet contains is being given to that material when combined with other material(s) or when used otherwise than as described herein.

In all cases, it is the responsibility of the user to determine the applicability of such information and recommendations and the suitability of any product for its own particular purpose. All materials may represent unknown hazards and should be used with caution.