# **S Permatex**

# SAFETY DATA SHEET

Revision Date 15-Sep-2016 Version 3

# 1. IDENTIFICATION

Product identifier

Product Name 84145 BLACK PLASTIC WELDER (ADHESIVE)

Other means of identification

Product Code R478-ADH1 Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Adhesive

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer AddressMay Also Be Distributed by:ITW PermatexITW Permatex Canada6875 Parkland Blvd.35 Brownridge Road, Unit 1Solon, OH 44139 USAHalton Hills, ON Canada L7G 0C6Telephone: (800) 924-6994

releptione. (600) 324-033

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

# 2. HAZARDS IDENTIFICATION

#### Classification

# **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 2 Sub-category A
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Flammable liquids	Category 2

# Label elements

#### **Emergency Overview**

# Danger

Harmful if swallowed Causes skin irritation May cause an allergic skin reaction Causes serious eye irritation Highly flammable liquid and vapor



Appearance White

Physical state Viscous liquid

**Odor** Methyl methacrylate

#### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

# **Precautionary Statements - Response**

Specific treatment (see supplemental first aid instructions on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

Do NOT induce vomiting

#### **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep cool

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

## Hazards not otherwise classified (HNOC)

Not applicable

# Other Information

- Not applicable

Unknown acute toxicity

17.5 % of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

# Substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
METHYL METHACRYLATE	80-62-6	30 - 60	*
METHACRYLIC ACID	79-41-4	5 - 10	*
DIMETHYLBENZYL HYDROPEROXIDE	80-15-9	1 - 5	*

# 4. FIRST AID MEASURES

#### **Description of first aid measures**

**General advice** Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

**Skin contact** IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower. Wash with soap and water. If skin irritation or rash occurs: Get medical

advice/attention. Wash contaminated clothing before reuse.

**Inhalation** IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Call a POISON CENTER or doctor/physician if you feel unwell. Rinse

mouth.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Highly flammable. Vapors may travel to source of ignition and flash back.

**Explosion data** 

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

**Personal precautions** ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes or

clothing. Wash thoroughly after handling.

Other Information Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological Information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with

inert absorbent material. Sweep up and shovel into suitable containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required. Take precautionary measures against static discharges. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

#### Conditions for safe storage, including any incompatibilities

Storage Conditions Store in a well-ventilated place. Keep cool.

Incompatible materials Strong oxidizing agents, Reducing agents

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
METHYL METHACRYLATE	STEL: 100 ppm	TWA: 100 ppm	IDLH: 1000 ppm
80-62-6	TWA: 50 ppm	TWA: 410 mg/m <sup>3</sup>	TWA: 100 ppm
		(vacated) TWA: 100 ppm	TWA: 410 mg/m <sup>3</sup>
		(vacated) TWA: 410 mg/m <sup>3</sup>	_
METHACRYLIC ACID	TWA: 20 ppm	(vacated) TWA: 20 ppm	TWA: 20 ppm
79-41-4		(vacated) TWA: 70 mg/m <sup>3</sup>	TWA: 70 mg/m <sup>3</sup>
		(vacated) S*	-

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls** 

Engineering Controls Showers

Eyewash stations Ventilation systems

# Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

**Respiratory protection**Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# Information on basic physical and chemical properties

Butyl acetate = 1

Air = 1

Physical state Viscous liquid

**Appearance** White

Odor Methyl methacrylate

Odor threshold 0.75 ppm

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No information available
Melting point / freezing point
Boiling point / boiling range
Flash point

No information available
No information available
100.5 °C / 212.9 °F
11.5 °C / 52.7 °F

Evaporation rate > 1

Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit: 12.5% Lower flammability limit: 1.6%

Vapor pressure 28 mmHg @ 68°F

Vapor density >3 Relative density 0.95

Water solubility Slightly soluble

Solubility in other solvents
Partition coefficient
Autoignition temperature
No information available
No information available
421°C (789.8°F)

Decomposition temperature
Kinematic viscosity
Dynamic viscosity
Explosive properties
No information available

**Other Information** 

Softening point No information available Molecular weight No information available

VOC Content (%) <50 g/L

DensityNo information availableBulk densityNo information available

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### Chemical stability

Stable under recommended storage conditions

#### Possibility of Hazardous Reactions

None under normal processing.

#### Conditions to avoid

Heat, flames and sparks.

# Incompatible materials

Strong oxidizing agents, Reducing agents

# **Hazardous Decomposition Products**

Carbon oxides

Nitrogen oxides (NOx)

# 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

**Inhalation** May cause irritation of respiratory tract.

**Eye contact** Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

**Skin contact** May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.

**Ingestion** May be harmful if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
METHYL METHACRYLATE	= 7900 mg/kg (Rat) = 7872 mg/kg	> 5 g/kg(Rabbit)	= 4632 ppm (Rat) 4 h
80-62-6	(Rat)		
METHACRYLIC ACID	= 1060 mg/kg (Rat)	500 - 1000 mg/kg (Rabbit) = 500	= 7.1 mg/L (Rat) 4 h
79-41-4		mg/kg(Rabbit)	
DIMETHYLBENZYL	= 382 mg/kg (Rat)	= 0.126 mL/kg ( Rabbit )	= 220 ppm (Rat) 4 h
HYDROPEROXIDE			
80-15-9			

### Information on toxicological effects

**Symptoms** No information available.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization No information available. Germ cell mutagenicity**No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
METHYL METHACRYLATE	-	Group 3	-	-
80-62-6		-		

IARC (International Agency for Research on Cancer)

Not classifiable as a human carcinogen

Target Organ Effects Eyes, Respiratory system, Skin.

# The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 1929 mg/kg ATEmix (dermal) 3269 mg/kg ATEmix (inhalation-dust/mist) 8.3 mg/l ATEmix (inhalation-vapor) 6948 mg/l

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

30 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

# Persistence and degradability

No information available.

#### Bioaccumulation

No information available.

## Mobility

No information available.

Chemical Name	Partition coefficient
METHYL METHACRYLATE 80-62-6	0.7
METHACRYLIC ACID 79-41-4	0.93

## Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
METHYL METHACRYLATE	Toxic
80-62-6	Ignitable
DIMETHYLBENZYL HYDROPEROXIDE	Toxic
80-15-9	Ignitable

# 14. TRANSPORT INFORMATION

DOT

**UN/ID no** 1133

**Proper shipping name:** Adhesives, Limited Quantity (LQ)

Hazard Class 3
Packing Group || |
Emergency Response Guide 128

Number

**IATA** 

**UN/ID no** ID 8000

Proper shipping name: Consumer commodity

Hazard Class 9 ERG Code 9L

**IMDG** 

**UN/ID no** 1133

Proper shipping name: Adhesives, Limited Quantity (LQ)

Hazard Class 3
Packing Group II
EmS-No F-E. S-D

# 15. REGULATORY INFORMATION

**International Inventories** 

Complies **TSCA DSL/NDSL** Complies **EINECS/ELINCS** Not determined Not determined **ENCS IECSC** Complies Complies **KECL** Complies **PICCS** Complies **AICS** 

Leaend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

# **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
METHYL METHACRYLATE - 80-62-6	1.0
DIMETHYLBENZYL HYDROPEROXIDE - 80-15-9	1.0

# SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

#### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
METHYL METHACRYLATE 80-62-6	1000 lb	-	-	Х

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
METHYL METHACRYLA	TE 1000 lb	-	RQ 1000 lb final RQ
80-62-6			RQ 454 kg final RQ
DIMETHYLBENZYL	10 lb	-	RQ 10 lb final RQ
HYDROPEROXIDE			RQ 4.54 kg final RQ
80-15-9			

# **US State Regulations**

# **California Proposition 65**

This product does not contain any Proposition 65 chemicals

#### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
METHYL METHACRYLATE	X	X	X
80-62-6			
METHACRYLIC ACID	X	X	X
79-41-4			
DIMETHYLBENZYL	X	X	X
HYDROPEROXIDE			
80-15-9			
BUTYLATED HYDROXY	X	X	X
TOLUENE			
128-37-0			

#### **U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

### **WHMIS Hazard Class**

Revision Date 15-Sep-2016

B2 - Flammable liquid, D2B - Toxic materials

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 3 Instability 0

HMIS Health hazards 2 Flammability 3 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 15-Sep-2016

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

# **Permatex.**

# SAFETY DATA SHEET

Revision Date 22-Apr-2015 Version 1

# 1. IDENTIFICATION

**Product identifier** 

Product Name 84145 BLACK PLASTIC WELDER (ACTIVATOR)

Other means of identification

Product Code R478-ACT-BL2

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Activator

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer AddressMay Also Be Distributed by:ITW PermatexITW Permatex Canada6875 Parkland Blvd.35 Brownridge Road, Unit 1Solon, OH 44139 USAHalton Hills, ON Canada L7G 0C6Telephone: (800) 924-6994

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

# 2. HAZARDS IDENTIFICATION

#### Classification

# **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2

# Label elements

# **Emergency Overview**

#### Danger

Causes skin irritation
May cause an allergic skin reaction
May cause respiratory irritation
Highly flammable liquid and vapor

# R478-ACT-BL2 - 84145 BLACK PLASTIC WELDER (ACTIVATOR)



Appearance Black Physical state Viscous liquid Odor Solvent

#### **Precautionary Statements - Prevention**

Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Wear protective gloves/protective clothing/eye protection/face protection
Wash face, hands and any exposed skin thoroughly after handling
Contaminated work clothing should not be allowed out of the workplace
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Use only non-sparking tools
Take precautionary measures against static discharge

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower If skin irritation or rash occurs: Get medical advice/attention IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing In case of fire: Use CO2, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep cool

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

#### Other Information

- Not applicable

Unknown acute toxicity 19.5 % of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
METHYL METHACRYLATE	80-62-6	60 - 100	*
CARBON BLACK	1333-86-4	0.1 - 1	*

# 4. FIRST AID MEASURES

# **Description of first aid measures**

**General advice** Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

\_\_\_\_\_

Revision Date 22-Apr-2015

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower. Wash with soap and water. If skin irritation or rash occurs: Get medical

advice/attention. Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

# 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Highly flammable. Vapors may travel to source of ignition and flash back.

**Explosion data** 

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Ensure adequate ventilation, especially in confined areas.

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Wash thoroughly after handling.

Environmental precautions

**Environmental precautions**Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological Information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with

·

inert absorbent material. Sweep up and shovel into suitable containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

### 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Incompatible materials Strong oxidizing agents, Reducing agents

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
METHYL METHACRYLATE STEL: 100 ppm		TWA: 100 ppm	IDLH: 1000 ppm
80-62-6	TWA: 50 ppm	TWA: 410 mg/m <sup>3</sup>	TWA: 100 ppm
		(vacated) TWA: 100 ppm	TWA: 410 mg/m <sup>3</sup>
		(vacated) TWA: 410 mg/m <sup>3</sup>	
CARBON BLACK	TWA: 3 mg/m³ inhalable fraction	TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup>
1333-86-4		(vacated) TWA: 3.5 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup>
			TWA: 0.1 mg/m³ Carbon black in
			presence of Polycyclic aromatic
			hydrocarbons PAH

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls** 

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Viscous liquid

# R478-ACT-BL2 - 84145 BLACK PLASTIC WELDER (ACTIVATOR)

Air = 1

AppearanceBlackOdorSolventOdor threshold0.75 ppm

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No information available
Melting point / freezing point
Boiling point / boiling range
Flash point
No information available
No information available
100.5 °C / 212.9 °F
11.5 °C / 52.7 °F

Flash point 11.5 °C / 52.7 °F Tag Closed Cup Evaporation rate >1 Butyl acetate = 1

Flammability (solid, gas) No information available Flammability Limit in Air

Upper flammability limit: 12.5% Lower flammability limit: 1.6%

Vapor pressure 28 mmHg @ 68°F

Vapor density >3

Relative density 0.95 Water solubility Slightly soluble

Solubility in other solvents
Partition coefficient
Autoignition temperature
Decomposition temperature
Kinematic viscosity
No information available
421 °F °C / 789.8 °F
No information available
No information available

Decomposition temperatureNo information availableKinematic viscosityNo information availableDynamic viscosityNo information availableExplosive propertiesNo information availableOxidizing propertiesNo information available

**Other Information** 

Softening point No information available Molecular weight No information available

VOC Content (%) <50 g/L

Density
No information available
Bulk density
No information available

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

## Chemical stability

Stable under recommended storage conditions

#### Possibility of Hazardous Reactions

None under normal processing.

### Conditions to avoid

Heat, flames and sparks.

#### Incompatible materials

Strong oxidizing agents, Reducing agents

#### **Hazardous Decomposition Products**

Carbon oxides Nitrogen oxides (NOx)

# 11. TOXICOLOGICAL INFORMATION

# Information on likely routes of exposure

**Inhalation** May cause irritation of respiratory tract.

**Eye contact** Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

**Skin contact** May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.

**Ingestion** Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
	= 7900 mg/kg (Rat) = 7872 mg/kg	> 5 g/kg (Rabbit)	= 4632 ppm (Rat) 4 h
80-62-6	( Rat )		
CARBON BLACK	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
1333-86-4			

### Information on toxicological effects

**Symptoms** No information available.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization Germ cell mutagenicity**No information available.
No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
METHYL METHACRYLATE	-	Group 3	-	-
80-62-6		-		
CARBON BLACK	A3	Group 2B	-	X
1333-86-4		-		

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

**Target Organ Effects** Eyes, Respiratory system, Skin.

# The following values are calculated based on chapter 3.1 of the GHS document $\,$ .

 ATEmix (oral)
 7921 mg/kg

 ATEmix (dermal)
 5036 mg/kg

 ATEmix (inhalation-vapor)
 4661 mg/l

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

20 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

# Persistence and degradability

No information available.

#### Bioaccumulation

No information available.

#### Mobility

No information available.

Chemical Name	Partition coefficient
METHYL METHACRYLATE	0.7
80-62-6	

### Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status	
METHYL METHACRYLATE	Toxic	
80-62-6	Ignitable	

# 14. TRANSPORT INFORMATION

DOT

**UN/ID no** 1133

Proper shipping name: Adhesives, Limited Quantity (LQ)

Hazard Class 3
Packing Group II
Emergency Response Guide 128

Number

<u>IATA</u>

**UN/ID** no ID 8000

Proper shipping name: Consumer commodity

Hazard Class 9 ERG Code 9L

<u>IMDG</u>

**UN/ID no** 1133

Proper shipping name: Adhesives, Limited Quantity (LQ)

Hazard Class 3
Packing Group

**EmS-No** F-E, S-D

# 15. REGULATORY INFORMATION

**International Inventories** 

**TSCA** Complies **DSL/NDSL** Complies **EINECS/ELINCS** Not determined **ENCS** Not determined **IECSC** Complies **KECL** Complies **PICCS** Complies **AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances **IECSC** - China Inventory of Existing Chemical Substances

# R478-ACT-BL2 - 84145 BLACK PLASTIC WELDER (ACTIVATOR)

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

## **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
METHYL METHACRYLATE - 80-62-6	1.0
SARA 311/312 Hazard Categories	
Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

#### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
METHYL METHACRYLATE 80-62-6	1000 lb	-	-	X

### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
METHYL METHACRYLATE	1000 lb	<del>-</del>	RQ 1000 lb final RQ
80-62-6			RQ 454 kg final RQ

# **US State Regulations**

# **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
CARBON BLACK - 1333-86-4	*Carcinogen (airborne, unbound particles of respirable size)

<sup>• \*</sup>The asterisked chemical(s) listed are not subject to Proposition 65 because they are not airborne in the finished product U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
METHYL METHACRYLATE	X	X	X
80-62-6			
CARBON BLACK	X	X	X
1333-86-4			

# U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

## **WHMIS Hazard Class**

B2 - Flammable liquid, D2B - Toxic materials

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 3 Instability 0 -

Health hazards 2 Flammability 3 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Revision Date 22-Apr-2015

### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**