

Solution 1800 General Purpose Anti-Seize

Page: 1 of 7 Printed: 05/05/2015 Revision: 05/05/2015

Supersedes Revision: 07/07/2012

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code: L-12966

Product Name: Solution 1800 General Purpose Anti-Seize

Company Name: MRO Solutions, LLC Phone Number: 5645 W. Howard St. +1 (847)588-2480

Niles, IL 60714

Web site address: http://www.mrosolutions.com/

Emergency Contact: CHEMTREC +1 (800)424-9300

2. HAZARDS IDENTIFICATION

Specific Target Organ Toxicity (repeated exposure), Category 1 Serious Eye Damage/Eye Irritation, Category 2A





GHS Signal Word: Danger

GHS Hazard Phrases: H319 - Causes serious eye irritation.

H372 - Causes damage to organs (lungs) through prolonged or repeated exposure.

GHS Precaution Phrases: P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases: P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+313 - If eye irritation

persists, get medical advice/attention.

P314 - Get medical attention/advice if you feel unwell.

GHS Storage and Disposal

Phrases:

P501 - Dispose of contents and containers in accordance with local, regional, national,

and international regulations.

Hazard Rating System:



Potential Health Effects (Acute and Chronic):

Preexisting pulmonary and dermatological disorders may be aggravated by exposure to hazardous components. Repeated or prolonged inhalation of graphite or carbon dusts may cause pulmonary fibrosis, emphysema, and pneumoconiosis. The severity of these effects is greatly influenced by the presence of other harmful mineral dusts, most notably crystalline silica. This product contains encapsulated metal powder containing copper and zinc and encapsulated silica. No exposure to free metal powder or free, respirable silica is anticipated during normal use of this product. Inhalation of free, respirable silica may cause silicosis or other serious delayed lung injury. Metal powder and/or silica may be released by grinding or machining of cured compound or coated materials. Repeated or prolonged exposure to metal dust may cause metal-fume fever, metallic taste, and discoloration of the skin and hair. Use NIOSH-approved dust/mist respirator when grinding or machining coated items.

Inhalation: May cause irritation to the respiratory tract. Inhalation of dusts at levels above

recommended exposure limits may cause a metallic or sweet taste.

Skin Contact: May cause mild skin irritation. Prolonged and/or repeated contact may cause irritation

and/or dermatitis.



Solution 1800 General Purpose Anti-Seize

Page: 2 of 7 Printed: 05/05/2015

Revision: 05/05/2015 Supersedes Revision: 07/07/2012

Eye Contact: Dust may cause mechanical irritation. May cause tearing, redness, and swelling. May

result in corneal injury.

Ingestion: No hazard expected in normal industrial use. May be harmful if swallowed. May cause

gastrointestinal irritation with nausea, vomiting and diarrhea.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| CAS # Hazardous Components (Chemical Name) | | Concentration |
|--|--------------------------------|---------------|
| 64742-52-5 | Aliphatic petroleum distillate | 68.0 % |
| 7782-42-5 | Graphite | 28.0 % |
| 112945-52-5 | Silica, amorphous treated | 1.00 % |
| 7429-90-5 | Aluminum | 2.00 % |
| 7440-50-8 | Copper | 1.00 % |

4. FIRST AID MEASURES

Emergency and First Aid

Procedures:

In Case of Inhalation: Remove from exposure and move to fresh air immediately. If breathing is difficult, give

oxygen. If breathing has ceased apply artificial respiration using oxygen and a suitable

mechanical device such as a bag and a mask. Get medical aid.

In Case of Skin Contact: Flush skin with plenty of water for at least 15 minutes while removing contaminated

clothing and shoes. Gently wash with plenty of soap and water. Get medical attention if

irritation persists. Wash contaminated clothing separately before reuse.

In Case of Eye Contact: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and

lower eyelids. Remove contact lenses, if present and easy to do after 5 minutes and

continue rinsing for an additional 15 minutes. Get medical aid.

In Case of Ingestion: Do NOT induce vomiting. If victim is conscious and alert, give 2-4 cupfuls of milk or

water. Never give anything by mouth to an unconscious person. Get medical aid

immediately. Call a poison control center.

Signs and Symptoms Of

Exposure:

Symptoms may not be readily apparent. Get medical advice/attention.

Note to Physician: Treat symptomatically and supportively. Show this safety data sheet to the doctor in

attendance.

5. FIRE FIGHTING MEASURES

Flash Pt: 302 F (150 C) Method Used: Pensky-Marten Closed Cup

Explosive Limits: LEL: No data. UEL: No data.

Autoignition Pt: No data.

Suitable Extinguishing Media: Foam, CO2, Dry Chemical, Water Fog. If water is used, fog nozzles are preferred.

Fire Fighting Instructions: As in any fire, wear a self-contained breathing apparatus in pressure-demand,

MSHA/NIOSH approved (or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Containers may explode in the heat of a fire. Use water spray to keep fire-exposed

containers cool.

Flammable Properties and

Hazards:

High temperatures and fire conditions can result in the formation of carbon monoxide and

carbon dioxide.



SAFETY DATA SHEET Solution 1800 General Purpose Anti-Seize

Page: 3 of 7 Printed: 05/05/2015

Revision: 05/05/2015

Supersedes Revision: 07/07/2012

6. ACCIDENTAL RELEASE MEASURES

Protective Precautions, Protective Equipment and Emergency Procedures:

Use proper personal protective equipment as indicated in Section 8.

Environmental Precautions:

Do not empty into drains. Material that cannot be recovered or reused should be

disposed of in accordance with all Federal, State and Local regulations.

Steps To Be Taken In Case Material Is Released Or Spilled:

Spills/Leaks: Provide ventilation. Avoid breathing vapors, mist or gas. Remove all sources of ignition. Sweep up or absorb material, then place into a suitable clean, dry, closed

container for disposal.

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:

Avoid contact with skin and eyes. Avoid ingestion and inhalation. Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Use with adequate ventilation.

Do not reuse empty containers without first having them commercially cleaned or reconditioned. Follow all SDS/label precautions even after container is emptied because they may retain product residues.

Precautions To Be Taken in

Other Precautions:

Storing:

Store in a cool, dry, well-ventilated area away from incompatible substances. Store away from heat. Store in a tightly closed container. Keep container closed when not in use.

Keep out of reach of children. Handle in accordance with good industrial hygiene and

safety practices.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

| CAS# | Partial Chemical Name | OSHA TWA | ACGIH TWA | Other Limits |
|-------------|--------------------------------|---------------------------------|--|--------------|
| 64742-52-5 | Aliphatic petroleum distillate | No data. | No data. | No data. |
| 7782-42-5 | Graphite | PEL: 532.5 ppm/15 mppcf | TLV: 2 mg/m3 (resp. except fibers) | No data. |
| 112945-52-5 | Silica, amorphous treated | No data. | No data. | No data. |
| 7429-90-5 | Aluminum | PEL: 15 (dust); 5 (resp.) mg/m3 | TLV: 1 mg/m3 (resp.) | No data. |
| 7440-50-8 | Copper | PEL: 0.1 (fume)/ 1.0 (dust) | TLV: 0.2 mg/m3 (fume) 1 mg/m3(dust/mist) | No data. |

Respiratory Equipment (Specify Type):

Not required under normal use conditions. Avoid breathing vapors or dusts. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use approved air line type respirator or hood. Self-contained breathing apparatus is required for vapor concentrations above PEL/TLV

limits.

Eye Protection: Safety glasses, chemical goggles, and/or face shield should be worn.

Not required under normal use conditions. Solvent resistant gloves required for prolonged **Protective Gloves:**

or repeated contact.

Other Protective Clothing:

Engineering Controls (Ventilation etc.):

Wear appropriate protective clothing to prevent skin exposure. Chemical resistant apron. Use adequate general or local exhaust ventilation to minimize exposure levels. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety

shower.

Work/Hygienic/Maintenance

Practices:

General industrial hygiene practice.



SAFETY DATA SHEETSolution 1800 General Purpose Anti-Seize

Page: 4 of 7
Printed: 05/05/2015

Supersedes Revision: 07/07/2012

Revision: 05/05/2015

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States: [] Gas [] Liquid [X] Solid
Appearance and Odor: Appearance: Metallic. Grayish. Paste.

Odor: Slight. Petroleum-like.

Melting Point: NA

Boiling Point: 500 C (932 F) **Autoignition Pt:** No data.

Flash Pt: 302 F (150 C) Method Used: Pensky-Marten Closed Cup

Explosive Limits: LEL: No data. UEL: No data.

Specific Gravity (Water = 1): 1.17

Density: NA

Vapor Pressure (vs. Air or No data.

mm Hg):

Vapor Density (vs. Air = 1): Heavier than air Evaporation Rate: Slower than ether

Solubility in Water: Nil
Percent Volatile: No data.

10. STABILITY AND REACTIVITY

Stability: Unstable [] Stable [X]

Conditions To Avoid - High temperatures, Incompatible materials.

Instability:

Incompatibility - Materials To Strong oxidizing agents, Strong acids, Strong bases, nitrates, nitrite, chlorinated

Avoid: hydrocarbons, magnesium, chlorides. diborane. palladium. selenium. manganese.

potassium chlorate. sodium carbonate. sulfates.

Hazardous Decomposition or High temperatures and fire conditions can result in the formation of carbon monoxide and

Byproducts: carbon dioxide.

Possibility of Hazardous Will occur [] Will not occur [X]

Reactions:

Conditions To Avoid - No data available.

Hazardous Reactions:



Solution 1800 General Purpose Anti-Seize

Printed: 05/05/2015 Revision: 05/05/2015

Page: 5 of 7

Supersedes Revision: 07/07/2012

11. TOXICOLOGICAL INFORMATION

Toxicological Information: Epidemiology: No information available.

Teratogenicity: No information available.

Reproductive Effects: No information available.

Mutagenicity: No information available. Neurotoxicity: No information available.

Other Studies: CAS# 64742-52-5:

Acute toxicity, LD, Oral, Rat, > 5.0 mg/kg

Other Studies: CAS # 112945-52-5:

Acute toxicity, LD50, Oral, Rat, 3160 mg / kg.

Other Studies: CAS# 7440-50-8:

Acute toxicity, LD50, Oral, Mouse, 413 mg / kg.

Irritation or Corrosion: Other Studies: CAS# 64742-52-5:

Standard Draize Test, Skin, Species: Rabbit, 500.0 mg.

Carcinogenicity/Other

Information:

This product contains encapsulated silicon dioxide (quartz, silica). No exposure to free, respirable silica is anticipated during normal use of this product. Free, respirable silica has been listed as a confirmed human carcinogen by NTP and IARC. Inhalation of free, respirable silica may cause silicosis or other serious delayed lung injury. Silica may be released by grinding or machining of coated materials. Use NIOSH-approved dust/mist

respirator when grinding or machining coated items.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

12. ECOLOGICAL INFORMATION

General Ecological

Information:

Environmental: No information available.

Physical: No information available. Other Studies: CAS# 7440-50-8:

LC50, Striped Bass (Morone saxatilis), larvae, 24 ug/L, 96H

LC50, Water flea (Daphnia lumholtzi), 9.4 ug/L, 96H.

Other Studies: CAS# 7429-90-5:

LC50, Rainbow trout (Oncorhynchus mykiss), embryo(s), 120 ug/L, 96H

LC50, Western mosquitofish (Gambina affinis), 56 ug/L, 96H.

Persistence and

Degradability:

No data available.

Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification. Observe all federal,

state, and local environmental regulations.



Solution 1800 General Purpose Anti-Seize

Page: 6 of 7 Printed: 05/05/2015

Revision: 05/05/2015 Supersedes Revision: 07/07/2012

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Not regulated as a hazardous material.

DOT Hazard Class: UN/NA Number:

7440-50-8

Copper

15. REGULATORY INFORMATION

| EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists | | | | | | | |
|---|--------------------------------------|---|--------------|----------------------|--|--|--|
| CAS# | Hazardous Components (Chemical Name) | S. 302 (EHS) | S. 304 RQ | S. 313 (TRI) | | | |
| 64742-52-5 | Aliphatic petroleum distillate | No | No | No | | | |
| 7782-42-5 | Graphite | No | No | No | | | |
| 112945-52-5 | Silica, amorphous treated | No | No | No | | | |
| 7429-90-5 | Aluminum | No | No | Yes | | | |
| 7440-50-8 | Copper | No | Yes 5000 LB | Yes-Cat. N100 | | | |
| CAS# | Hazardous Components (Chemical Name) | Other US EPA or State Lists | | | | | |
| 64742-52-5 | Aliphatic petroleum distillate | TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No | | | | | |
| 7782-42-5 | Graphite | TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: Title 8; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 3325; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: Yes | | | | | |
| 112945-52-5 | Silica, amorphous treated | TSCA: No; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No | | | | | |
| 7429-90-5 | Aluminum | TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 0054; NY Part 597: No; PA HSL: Yes - E; SC TAP: No; WI Air: Yes | | | | | |
| 7440-50-8 | Copper | TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: CMR, Part 5; NC TAP: No; NJ EHS: Yes - 0528; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: No; WI Air: Yes | | | | | |
| CAS# | Hazardous Components (Chemical Name) | International Regu | latory Lists | | | | |
| 64742-52-5 | Aliphatic petroleum distillate | | | lo; Mexico INSQ: Yes | | | |
| 7782-42-5 | Graphite | Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes | | | | | |
| 112945-52-5 | Silica, amorphous treated | Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes | | | | | |
| 7429-90-5 | Aluminum | Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes | | | | | |

Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes



SAFETY DATA SHEET Solution 1800 General Purpose Anti-Seize

Page: 7 of 7 Printed: 05/05/2015

Revision: 05/05/2015

Supersedes Revision: 07/07/2012

16. OTHER INFORMATION

Revision Date: 05/05/2015
Preparer Name: Crystal Maira
Additional Information About No data available.

This Product:

Company Policy or

Disclaimer:

Information presented herein is believed to be accurate and reliable to the best of our knowledge. However, we

make no warranty or merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process. Users should make their own investigations to determine the suitability of the information for their

particular purposes.