

## 1. Identification

<b>Product identifier</b>	<b>TRUE BLUE 085205-0</b>		
<b>Other means of identification</b>			
<b>Product Code</b>	09549 704794 713		
<b>Recommended use</b>	Not available.		
<b>Manufacturer/Importer/Supplier/Distributor information</b>			
<b>Manufacturer</b>			
<b>Company name</b>	Quest Industrial Products, LLC.		
<b>Address</b>	N92 W14701 Anthony Avenue Menomonee Falls, WI 53051 United States		
<b>Telephone</b>	General Assistance	(262) 255-9500	
<b>Website</b>	quest-ip.com		
<b>E-mail</b>	info@quest-ip.com		
<b>Emergency phone number</b>	Chemtrec Phone	800-424-9300	

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable aerosols	Category 2
	Gases under pressure	Liquefied gas
<b>Health hazards</b>	Serious eye damage/eye irritation	Category 2A
	Germ cell mutagenicity	Category 1B
	Carcinogenicity	Category 1B
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 3
<b>OSHA defined hazards</b>	Not classified.	

### Label elements



<b>Signal word</b>	Danger
<b>Hazard statement</b>	Flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.
<b>Precautionary statement</b>	
<b>Prevention</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

<b>Response</b>	If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.
<b>Storage</b>	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
<b>Supplemental information</b>	83.97% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 83.97% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
ACETONE		67-64-1	20 to <30
PROPANE		74-98-6	10 to <20
PROPYLENE GLYCOL METHYL ETHER ACETATE		108-65-6	10 to <20
BARIUM SULFATE		7727-43-7	5 to <10
N-BUTANE		106-97-8	5 to <10
2-PENTANONE		107-87-9	1 to <5
PHTHALOCYANINE BLUE		147-14-8	1 to <5
TITANIUM DIOXIDE		13463-67-7	1 to <5
XYLENE		1330-20-7	1 to <5
1 METHOXY-2-PROPANOL		107-98-2	0.1 to <1
1,2,4 TRIMETHYLBENZENE		95-63-6	0.1 to <1
2-BUTOXYETHANOL		111-76-2	0.1 to <1
ALIPHATIC SOLVENT MIXTURE		64741-41-9	0.1 to <1
ALUMINUM HYDROXIDE		21645-51-2	0.1 to <1
CALCIUM CARBONATE		471-34-1	0.1 to <1
COPPER		7440-50-8	0.1 to <1
ETHYLBENZENE		100-41-4	0.1 to <1
ISOBUTYL ALCOHOL		78-83-1	0.1 to <1
KAOLIN		1332-58-7	0.1 to <1
MEDIUM ALIPHATIC SOLVENT NAPHTHA		64742-88-7	0.1 to <1
METHYL ETHYL KETOXIME		96-29-7	0.1 to <1
MINERAL SPIRITS		8052-41-3	0.1 to <1
POLYCHLORO COPPER PHTHALOCYANINE (AS CU)		1328-53-6	0.1 to <1
PROPYLENE GLYCOL		57-55-6	0.1 to <1
SILICA, CRYSTALLINE QUARTZ		14808-60-7	0.1 to <1
SILICA, CRYSTALLINE-CRISTOBALITE		14464-46-1	0.1 to <1
ZIRCONIUM OCTOATE		22464-99-9	0.1 to <1
Other components below reportable levels			10 to <20

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Skin contact</b>	Rinse skin with water/shower. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
<b>Most important symptoms/effects, acute and delayed</b>	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire fighting equipment/instructions</b>	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
<b>General fire hazards</b>	Flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe the mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.  Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Do not breathe mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

### Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
2-BUTOXYETHANOL (CAS 111-76-2)	PEL	240 mg/m <sup>3</sup>	
2-PENTANONE (CAS 107-87-9)	PEL	50 ppm 700 mg/m <sup>3</sup>	
ACETONE (CAS 67-64-1)	PEL	200 ppm 2400 mg/m <sup>3</sup>	
BARIUM SULFATE (CAS 7727-43-7)	PEL	1000 ppm 5 mg/m <sup>3</sup>	Respirable fraction.
CALCIUM CARBONATE (CAS 471-34-1)	PEL	15 mg/m <sup>3</sup> 5 mg/m <sup>3</sup>	Total dust. Respirable fraction.
COPPER (CAS 7440-50-8)	PEL	15 mg/m <sup>3</sup> 1 mg/m <sup>3</sup>	Total dust. Dust and mist.
ETHYLBENZENE (CAS 100-41-4)	PEL	0.1 mg/m <sup>3</sup> 435 mg/m <sup>3</sup>	Fume.
ISOBUTYL ALCOHOL (CAS 78-83-1)	PEL	100 ppm 300 mg/m <sup>3</sup>	
KAOLIN (CAS 1332-58-7)	PEL	100 ppm 5 mg/m <sup>3</sup>	Respirable fraction.
MINERAL SPIRITS (CAS 8052-41-3)	PEL	15 mg/m <sup>3</sup> 2900 mg/m <sup>3</sup>	Total dust.
PROPANE (CAS 74-98-6)	PEL	500 ppm 1800 mg/m <sup>3</sup>	
TITANIUM DIOXIDE (CAS 13463-67-7)	PEL	1000 ppm 15 mg/m <sup>3</sup>	Total dust.
XYLENE (CAS 1330-20-7)	PEL	435 mg/m <sup>3</sup>	

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
ZIRCONIUM OCTOATE (CAS 22464-99-9)	PEL	100 ppm 5 mg/m3	

**US. OSHA Table Z-3 (29 CFR 1910.1000)**

Components	Type	Value	Form
SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.
SILICA, CRYSTALLINE-CRISTOBA LITE (CAS 14464-46-1)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
		0.15 mg/m3	Total dust.
		0.05 mg/m3	Respirable.
		1.2 mppcf	Respirable.

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
1 METHOXY-2-PROPANOL (CAS 107-98-2)	STEL	100 ppm	
1,2,4 TRIMETHYLBENZENE (CAS 95-63-6)	TWA	50 ppm	
	TWA	25 ppm	
2-BUTOXYETHANOL (CAS 111-76-2)	TWA	20 ppm	
2-PENTANONE (CAS 107-87-9)	STEL	150 ppm	
ACETONE (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
ALUMINUM HYDROXIDE (CAS 21645-51-2)	TWA	1 mg/m3	Respirable fraction.
BARIUM SULFATE (CAS 7727-43-7)	TWA	5 mg/m3	Inhalable fraction.
ETHYLBENZENE (CAS 100-41-4)	TWA	20 ppm	
ISOBUTYL ALCOHOL (CAS 78-83-1)	TWA	50 ppm	
KAOLIN (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
MEDIUM ALIPHATIC SOLVENT NAPHTHA (CAS 64742-88-7)	TWA	200 mg/m3	Non-aerosol.
MINERAL SPIRITS (CAS 8052-41-3)	TWA	100 ppm	
N-BUTANE (CAS 106-97-8)	STEL	1000 ppm	
PHTHALOCYANINE BLUE (CAS 147-14-8)	TWA	1 mg/m3	Dust and mist.
POLYCHLORO COPPER PHTHALOCYANINE (AS CU) (CAS 1328-53-6)	TWA	0.2 mg/m3	Fume.
		1 mg/m3	Dust and mist.
SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7)	TWA	0.2 mg/m3	Fume.
		0.025 mg/m3	Respirable fraction.
SILICA, CRYSTALLINE-CRISTOBA LITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
TITANIUM DIOXIDE (CAS 13463-67-7)	TWA	10 mg/m3	
XYLENE (CAS 1330-20-7)	STEL	150 ppm	

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
ZIRCONIUM OCTOATE (CAS 22464-99-9)	TWA	100 ppm	
	STEL	10 mg/m3	
	TWA	5 mg/m3	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
1 METHOXY-2-PROPANOL (CAS 107-98-2)	STEL	540 mg/m3	
1,2,4 TRIMETHYLBENZENE (CAS 95-63-6)	TWA	150 ppm	
		360 mg/m3	
		100 ppm	
2-BUTOXYETHANOL (CAS 111-76-2)	TWA	125 mg/m3	
		25 ppm	
2-PENTANONE (CAS 107-87-9)	TWA	24 mg/m3	
		5 ppm	
ACETONE (CAS 67-64-1)	TWA	530 mg/m3	
		150 ppm	
BARIUM SULFATE (CAS 7727-43-7)	TWA	590 mg/m3	Respirable.
		250 ppm	
CALCIUM CARBONATE (CAS 471-34-1)	TWA	5 mg/m3	Total Respirable.
		10 mg/m3	
COPPER (CAS 7440-50-8)	TWA	1 mg/m3	Total Dust and mist.
	STEL	545 mg/m3	
ETHYLBENZENE (CAS 100-41-4)	TWA	125 ppm	
		435 mg/m3	
		100 ppm	
ISOBUTYL ALCOHOL (CAS 78-83-1)	TWA	150 mg/m3	
		50 ppm	
KAOLIN (CAS 1332-58-7)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
MEDIUM ALIPHATIC SOLVENT NAPHTHA (CAS 64742-88-7)	TWA	100 mg/m3	
MINERAL SPIRITS (CAS 8052-41-3)	Ceiling	1800 mg/m3	
	TWA	350 mg/m3	
N-BUTANE (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
PHTHALOCYANINE BLUE (CAS 147-14-8)	TWA	1 mg/m3	Dust and mist.
POLYCHLORO COPPER PHTHALOCYANINE (AS CU) (CAS 1328-53-6)	TWA	1 mg/m3	Dust and mist.
PROPANE (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	
SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
SILICA, CRYSTALLINE-CRISTOBA LITE (CAS 14464-46-1)	TWA	3 fibers/cm3	Fiber.
		3 fibers/cm3	Dust.

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
ZIRCONIUM OCTOATE (CAS 22464-99-9)	STEL	5 mg/m3	fibers, total dust
		5 mg/m3	Fiber, total
		10 mg/m3	
	TWA	5 mg/m3	

**US. Workplace Environmental Exposure Level (WEEL) Guides**

Components	Type	Value	Form
METHYL ETHYL KETOXIME (CAS 96-29-7)	TWA	36 mg/m3	
PROPYLENE GLYCOL (CAS 57-55-6)	TWA	10 ppm 10 mg/m3	Aerosol.
PROPYLENE GLYCOL METHYL ETHER ACETATE (CAS 108-65-6)	TWA	50 ppm	

**Biological limit values**

**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
2-BUTOXYETHANOL (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*
ACETONE (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
ETHYLBENZENE (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
XYLENE (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Exposure guidelines**

**US - California OELs: Skin designation**

- 1 METHOXY-2-PROPANOL (CAS 107-98-2) Can be absorbed through the skin.
- 2-BUTOXYETHANOL (CAS 111-76-2) Can be absorbed through the skin.
- PROPYLENE GLYCOL METHYL ETHER ACETATE (CAS 108-65-6) Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies**

- 2-BUTOXYETHANOL (CAS 111-76-2) Skin designation applies.

**US - Tennessee OELs: Skin designation**

- 2-BUTOXYETHANOL (CAS 111-76-2) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation**

- MEDIUM ALIPHATIC SOLVENT NAPHTHA (CAS 64742-88-7) Can be absorbed through the skin.

**US NIOSH Pocket Guide to Chemical Hazards: Skin designation**

- 2-BUTOXYETHANOL (CAS 111-76-2) Can be absorbed through the skin.

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

- 2-BUTOXYETHANOL (CAS 111-76-2) Can be absorbed through the skin.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection**

**Hand protection** For prolonged or repeated skin contact use suitable protective gloves.

**Other** Wear suitable protective clothing.

<b>Respiratory protection</b>	In case of insufficient ventilation, wear suitable respiratory equipment.
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>General hygiene considerations</b>	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

### Appearance

<b>Physical state</b>	Liquid.
<b>Form</b>	Aerosol. Liquefied gas.
<b>Color</b>	Not available.
<b>Odor</b>	Not available.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	-305.68 °F (-187.6 °C) estimated
<b>Initial boiling point and boiling range</b>	-43.78 °F (-42.1 °C) estimated
<b>Flash point</b>	-156.0 °F (-104.4 °C) estimated
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	1.9 % estimated
<b>Flammability limit - upper (%)</b>	12.8 % estimated
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	2499.24 hPa estimated
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	550 °F (287.78 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Density</b>	7.12 lbs/gal
<b>Explosive properties</b>	Not explosive.
<b>Flammability class</b>	Flammable IA estimated
<b>Heat of combustion (NFPA 30B)</b>	22.92 kJ/g estimated
<b>Oxidizing properties</b>	Not oxidizing.
<b>Percent volatile</b>	69.1
<b>Specific gravity</b>	0.86
<b>VOC</b>	4.27 lbs/gal Regulatory 3.06 lbs/gal Material 511.32 g/l Regulatory 366.97 g/l Material



## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong acids. Strong oxidizing agents. Nitrates. Aluminum. Halogens. Phosphorus. Fluorine. Chlorine.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
<b>Skin contact</b>	No adverse effects due to skin contact are expected.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Expected to be a low ingestion hazard.

**Symptoms related to the physical, chemical and toxicological characteristics** May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

### Information on toxicological effects

**Acute toxicity** Narcotic effects.

Components	Species	Test Results
1 METHOXY-2-PROPANOL (CAS 107-98-2)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	13 g/kg
<b>Inhalation</b>		
LC50	Guinea pig	15000 mg/l, 10 Hours
	Rat	54.6 mg/l, 4 Hours
<b>Oral</b>		
LD50	Mouse	10.8 g/kg
	Rabbit	5.3 g/kg
	Rat	5.71 g/kg
1,2,4 TRIMETHYLBENZENE (CAS 95-63-6)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 3160 mg/kg
<b>Inhalation</b>		
LC50	Rat	> 2000 ppm, 48 Hours
<b>Oral</b>		
LD50	Rat	6 g/kg
2-BUTOXYETHANOL (CAS 111-76-2)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	400 mg/kg
<b>Inhalation</b>		
LC50	Mouse	700 ppm, 7 Hours
	Rat	450 ppm, 4 Hours

Components	Species	Test Results
<b>Oral</b>		
LD50	Guinea pig	1.2 g/kg
	Mouse	1.2 g/kg
	Rabbit	0.32 g/kg
	Rat	560 mg/kg
2-PENTANONE (CAS 107-87-9)		
<b><u>Acute</u></b>		
<b>Oral</b>		
LD50	Rat	3.73 g/kg
ACETONE (CAS 67-64-1)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	> 15800 mg/kg
<b>Inhalation</b>		
LC50	Rat	76 mg/l, 4 Hours
<b>Oral</b>		
LD50	Mouse	3000 mg/kg
	Rat	5800 mg/kg
ALUMINUM HYDROXIDE (CAS 21645-51-2)		
<b><u>Acute</u></b>		
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
CALCIUM CARBONATE (CAS 471-34-1)		
<b><u>Acute</u></b>		
<b>Oral</b>		
LD50	Mouse	6450 mg/kg
	Rat	6450 mg/kg
ETHYLBENZENE (CAS 100-41-4)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	17800 mg/kg
<b>Oral</b>		
LD50	Rat	3500 mg/kg
ISOBUTYL ALCOHOL (CAS 78-83-1)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	3392 mg/kg
<b>Inhalation</b>		
LC50	Rat	8000 ppm, 4 Hours
LD50	Guinea pig	19.9 mg/l
	Rabbit	26.25 mg/l
	Rat	19.2 mg/l
<b>Oral</b>		
LD50	Mouse	3500 mg/kg
	Rat	2.46 g/kg
KAOLIN (CAS 1332-58-7)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rat	> 5000 mg/kg

Components	Species	Test Results
<b>Oral</b> LD50	Rat	> 5000 mg/kg
N-BUTANE (CAS 106-97-8)		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Mouse	680 mg/l, 2 Hours
	Rat	658 mg/l, 4 Hours
PROPANE (CAS 74-98-6)		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Rat	> 1442.847 mg/l, 15 Minutes
PROPYLENE GLYCOL (CAS 57-55-6)		
<b>Acute</b>		
<b>Oral</b>		
LD50	Guinea pig	18.4 g/kg
	Mouse	23.9 g/kg
	Rabbit	18 g/kg
	Rat	30 g/kg
XYLENE (CAS 1330-20-7)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 43 g/kg
<b>Inhalation</b>		
LC50	Mouse	3907 mg/l, 6 Hours
	Rat	6350 mg/l, 4 Hours
<b>Oral</b>		
LD50	Mouse	1590 mg/kg
	Rat	3523 - 8600 mg/kg

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

**Serious eye damage/eye irritation** Causes serious eye irritation.

**Respiratory or skin sensitization**

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity** May cause genetic defects.

**Carcinogenicity** May cause cancer.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

2-BUTOXYETHANOL (CAS 111-76-2)	3 Not classifiable as to carcinogenicity to humans.
ETHYLBENZENE (CAS 100-41-4)	2B Possibly carcinogenic to humans.
MINERAL SPIRITS (CAS 8052-41-3)	3 Not classifiable as to carcinogenicity to humans.
SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7)	1 Carcinogenic to humans.
SILICA, CRYSTALLINE-CRISTOBALITE (CAS 14464-46-1)	1 Carcinogenic to humans.
TITANIUM DIOXIDE (CAS 13463-67-7)	2B Possibly carcinogenic to humans.
XYLENE (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not regulated.

**US. National Toxicology Program (NTP) Report on Carcinogens**

SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7)	Known To Be Human Carcinogen.
SILICA, CRYSTALLINE-CRISTOBALITE (CAS 14464-46-1)	Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

<b>Reproductive toxicity</b>	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging fertility or the unborn child.
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness and dizziness.
<b>Specific target organ toxicity - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	Not an aspiration hazard.
<b>Chronic effects</b>	Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
1,2,4 TRIMETHYLBENZENE (CAS 95-63-6)		
<b>Aquatic</b>		
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> ) 7.19 - 8.28 mg/l, 96 hours
2-BUTOXYETHANOL (CAS 111-76-2)		
<b>Aquatic</b>		
Fish	LC50	Inland silverside ( <i>Menidia beryllina</i> ) 1250 mg/l, 96 hours
2-PENTANONE (CAS 107-87-9)		
<b>Aquatic</b>		
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> ) 1190 - 1290 mg/l, 96 hours
ACETONE (CAS 67-64-1)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> ) 10294 - 17704 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout ( <i>Oncorhynchus mykiss</i> ) 4740 - 6330 mg/l, 96 hours
BARIUM SULFATE (CAS 7727-43-7)		
<b>Aquatic</b>		
Crustacea	EC50	Tubificid worm ( <i>Tubifex tubifex</i> ) 28.61 - 38.03 mg/l, 48 hours
CALCIUM CARBONATE (CAS 471-34-1)		
<b>Aquatic</b>		
Fish	LC50	Western mosquitofish ( <i>Gambusia affinis</i> ) > 56000 mg/l, 96 hours
COPPER (CAS 7440-50-8)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> ) 0.036 mg/l, 48 hours
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> ) 0.0319 - 0.0544 mg/l, 96 hours
ETHYLBENZENE (CAS 100-41-4)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> ) 1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> ) 7.5 - 11 mg/l, 96 hours
ISOBUTYL ALCOHOL (CAS 78-83-1)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea ( <i>Daphnia pulex</i> ) 950 - 1200 mg/l, 48 hours
Fish	LC50	Bleak ( <i>Alburnus alburnus</i> ) 1000 - 3000 mg/l, 96 hours
METHYL ETHYL KETOXIME (CAS 96-29-7)		
<b>Aquatic</b>		
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> ) 777 - 914 mg/l, 96 hours
PROPYLENE GLYCOL (CAS 57-55-6)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> ) > 10000 mg/l, 48 hours

Components	Species	Test Results
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> ) 710 mg/l, 96 hours
TITANIUM DIOXIDE (CAS 13463-67-7)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> ) > 1000 mg/l, 48 hours
Fish	LC50	Mummichog ( <i>Fundulus heteroclitus</i> ) > 1000 mg/l, 96 hours
XYLENE (CAS 1330-20-7)		
<b>Aquatic</b>		
Fish	LC50	Bluegill ( <i>Lepomis macrochirus</i> ) 7.711 - 9.591 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

#### Bioaccumulative potential

##### Partition coefficient n-octanol / water (log Kow)

2-BUTOXYETHANOL	0.83
2-PENTANONE	0.91
ACETONE	-0.24
ETHYLBENZENE	3.15
ISOBUTYL ALCOHOL	0.76
MINERAL SPIRITS	3.16 - 7.15
N-BUTANE	2.89
PROPANE	2.36
PROPYLENE GLYCOL	-0.92
XYLENE	3.12 - 3.2

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

### 14. Transport information

#### DOT

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, Flammable
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>Packing group</b>	Not applicable.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	N82
<b>Packaging exceptions</b>	306
<b>Packaging non bulk</b>	None
<b>Packaging bulk</b>	None

**IATA**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, Flammable
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	No.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed.
<b>Cargo aircraft only</b>	Allowed.

**IMDG**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, Flammable
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No.
<b>EmS</b>	Not available.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.

**DOT****IATA; IMDG****General information**

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

## 15. Regulatory information

### US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

1 METHOXY-2-PROPANOL (CAS 107-98-2)	Listed.
2-BUTOXYETHANOL (CAS 111-76-2)	Listed.
2-PENTANONE (CAS 107-87-9)	Listed.
ACETONE (CAS 67-64-1)	Listed.
BARIUM SULFATE (CAS 7727-43-7)	Listed.
COPPER (CAS 7440-50-8)	Listed.
ETHYLBENZENE (CAS 100-41-4)	Listed.
ISOBUTYL ALCOHOL (CAS 78-83-1)	Listed.
N-BUTANE (CAS 106-97-8)	Listed.
PHTHALOCYANINE BLUE (CAS 147-14-8)	Listed.
POLYCHLORO COPPER PHTHALOCYANINE (AS CU) (CAS 1328-53-6)	Listed.
PROPANE (CAS 74-98-6)	Listed.
XYLENE (CAS 1330-20-7)	Listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

<b>Hazard categories</b>	Immediate Hazard - Yes
	Delayed Hazard - Yes
	Fire Hazard - Yes
	Pressure Hazard - No
	Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312 Hazardous chemical** No

#### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
XYLENE	1330-20-7	1 to <5
1,2,4 TRIMETHYLBENZENE	95-63-6	0.1 to <1
2-BUTOXYETHANOL	111-76-2	0.1 to <1
COPPER	7440-50-8	0.1 to <1
ETHYLBENZENE	100-41-4	0.1 to <1

#### Other federal regulations

##### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ETHYLBENZENE (CAS 100-41-4)  
XYLENE (CAS 1330-20-7)

##### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

N-BUTANE (CAS 106-97-8)  
PROPANE (CAS 74-98-6)

**Safe Drinking Water Act (SDWA)** Not regulated.

##### Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

ACETONE (CAS 67-64-1) 6532

##### Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

ACETONE (CAS 67-64-1) 35 %WV

##### DEA Exempt Chemical Mixtures Code Number

ACETONE (CAS 67-64-1) 6532

##### FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

2-PENTANONE (CAS 107-87-9) Low priority

ACETONE (CAS 67-64-1)  
ISOBUTYL ALCOHOL (CAS 78-83-1)

Low priority  
Low priority

## US state regulations

### US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1 METHOXY-2-PROPANOL (CAS 107-98-2)  
1,2,4 TRIMETHYLBENZENE (CAS 95-63-6)  
2-BUTOXYETHANOL (CAS 111-76-2)  
ACETONE (CAS 67-64-1)  
ALIPHATIC SOLVENT MIXTURE (CAS 64741-41-9)  
COPPER (CAS 7440-50-8)  
ETHYLBENZENE (CAS 100-41-4)  
MEDIUM ALIPHATIC SOLVENT NAPHTHA (CAS 64742-88-7)  
MINERAL SPIRITS (CAS 8052-41-3)  
N-BUTANE (CAS 106-97-8)  
SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7)  
SILICA, CRYSTALLINE-CRISTOBALITE (CAS 14464-46-1)  
TITANIUM DIOXIDE (CAS 13463-67-7)  
XYLENE (CAS 1330-20-7)

### US. Massachusetts RTK - Substance List

1 METHOXY-2-PROPANOL (CAS 107-98-2)  
1,2,4 TRIMETHYLBENZENE (CAS 95-63-6)  
2-BUTOXYETHANOL (CAS 111-76-2)  
2-PENTANONE (CAS 107-87-9)  
ACETONE (CAS 67-64-1)  
BARIUM SULFATE (CAS 7727-43-7)  
CALCIUM CARBONATE (CAS 471-34-1)  
COPPER (CAS 7440-50-8)  
ETHYLBENZENE (CAS 100-41-4)  
ISOBUTYL ALCOHOL (CAS 78-83-1)  
KAOLIN (CAS 1332-58-7)  
MEDIUM ALIPHATIC SOLVENT NAPHTHA (CAS 64742-88-7)  
MINERAL SPIRITS (CAS 8052-41-3)  
N-BUTANE (CAS 106-97-8)  
PROPANE (CAS 74-98-6)  
SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7)  
SILICA, CRYSTALLINE-CRISTOBALITE (CAS 14464-46-1)  
TITANIUM DIOXIDE (CAS 13463-67-7)  
XYLENE (CAS 1330-20-7)

### US. New Jersey Worker and Community Right-to-Know Act

1 METHOXY-2-PROPANOL (CAS 107-98-2)  
1,2,4 TRIMETHYLBENZENE (CAS 95-63-6)  
2-BUTOXYETHANOL (CAS 111-76-2)  
2-PENTANONE (CAS 107-87-9)  
ACETONE (CAS 67-64-1)  
BARIUM SULFATE (CAS 7727-43-7)  
CALCIUM CARBONATE (CAS 471-34-1)  
COPPER (CAS 7440-50-8)  
ETHYLBENZENE (CAS 100-41-4)  
ISOBUTYL ALCOHOL (CAS 78-83-1)  
KAOLIN (CAS 1332-58-7)  
MEDIUM ALIPHATIC SOLVENT NAPHTHA (CAS 64742-88-7)  
N-BUTANE (CAS 106-97-8)  
PHTHALOCYANINE BLUE (CAS 147-14-8)  
POLYCHLORO COPPER PHTHALOCYANINE (AS CU) (CAS 1328-53-6)  
PROPANE (CAS 74-98-6)  
PROPYLENE GLYCOL (CAS 57-55-6)  
SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7)  
SILICA, CRYSTALLINE-CRISTOBALITE (CAS 14464-46-1)  
TITANIUM DIOXIDE (CAS 13463-67-7)  
XYLENE (CAS 1330-20-7)



## US. Pennsylvania Worker and Community Right-to-Know Law

1 METHOXY-2-PROPANOL (CAS 107-98-2)  
1,2,4 TRIMETHYLBENZENE (CAS 95-63-6)  
2-BUTOXYETHANOL (CAS 111-76-2)  
2-PENTANONE (CAS 107-87-9)  
ACETONE (CAS 67-64-1)  
BARIUM SULFATE (CAS 7727-43-7)  
CALCIUM CARBONATE (CAS 471-34-1)  
COPPER (CAS 7440-50-8)  
ETHYLBENZENE (CAS 100-41-4)  
ISOBUTYL ALCOHOL (CAS 78-83-1)  
KAOLIN (CAS 1332-58-7)  
MEDIUM ALIPHATIC SOLVENT NAPHTHA (CAS 64742-88-7)  
MINERAL SPIRITS (CAS 8052-41-3)  
N-BUTANE (CAS 106-97-8)  
PROPANE (CAS 74-98-6)  
PROPYLENE GLYCOL (CAS 57-55-6)  
SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7)  
SILICA, CRYSTALLINE-CRISTOBALITE (CAS 14464-46-1)  
TITANIUM DIOXIDE (CAS 13463-67-7)  
XYLENE (CAS 1330-20-7)

## US. Rhode Island RTK

1,2,4 TRIMETHYLBENZENE (CAS 95-63-6)  
2-BUTOXYETHANOL (CAS 111-76-2)  
ACETONE (CAS 67-64-1)  
COPPER (CAS 7440-50-8)  
ETHYLBENZENE (CAS 100-41-4)  
ISOBUTYL ALCOHOL (CAS 78-83-1)  
N-BUTANE (CAS 106-97-8)  
PROPANE (CAS 74-98-6)  
XYLENE (CAS 1330-20-7)

## US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

ETHYLBENZENE (CAS 100-41-4)	Listed: June 11, 2004
SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7)	Listed: October 1, 1988
TITANIUM DIOXIDE (CAS 13463-67-7)	Listed: September 2, 2011

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date	03-08-2015
Revision date	01-15-2016
Version #	03

Material name: TRUE BLUE 085205-0

09549 704794 713 Version #: 03 Revision date: 01-15-2016 Issue date: 03-08-2015

SDS US

17 / 18

**HMIS® ratings**

Health: 2\*  
Flammability: 3  
Physical hazard: 0

**NFPA ratings**

Health: 2  
Flammability: 3  
Instability: 0

**Disclaimer**

The information in the sheet was written based on the best knowledge and experience currently available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.

**Revision information**

This document has undergone significant changes and should be reviewed in its entirety.